# **Product Data Sheet**

## Leica DISTO™ D1

#### **Features**



- Range up to 40 m
- ±2 mm accuracy, 0.1 mm resolution
- X-range Power Technology
- Illuminated display
- Up to 10'000 measurements with 2 x AAA batteries
- Bluetooth® Technology for error-free data transfer
- Works with DISTO<sup>™</sup> Plan App (iOS and Android) and DISTO<sup>™</sup> transfer (Windows)

#### Technical data

	Leica DISTO™ D1	
Accuracy with favourable conditions *	2.0 mm / 0.08 in ***	
Accuracy with unfavourable conditions **	3 mm / 1/8" ***	
Range with favourable conditions *	0.2 - 40 m / 0.6 - 120 ft ***	
Range with unfavourable conditions **	0.2 - 30 m / 0.6 - 100 ft ***	
Smallest unit displayed	0.1 mm / 1/32 in	
X-Range Power Technology	yes	
Laser class	2	
Laser type	635 nm, <1 mW	
ø laser point   at distances	6 / 30 / 60 mm   10 / 50 / 100 m	
Protection class	IP54 (dust- and splash water protected)	
Auto. laser switch off after	90 s	
Auto. power switch off after	180 s	
Bluetooth® Smart	Bluetooth® v4.0	
Range of Bluetooth® Smart	up to 10 m	
Datton durability (2 v AAA)	up to 10'000 measurements	
Battery durability (2 x AAA)	up to 20 hours operation time	
Dimension (H x D x W)	115 x 43.5 x 23.5 mm   4.53 x 1.71 x 0.93 in	
Weight (with batteries)	87 g/ 3.07 oz	
Temperature range Storage   Operation	-25 to 70°C / -13 to 158°F   0 to 40°C / 32 to 104°F	

<sup>\*</sup> favourable conditions: white and diffuse reflecting target (white painted wall), low background illumination and moderate temperatures.

## **Functions**

Distance measuring	Permanent measuring	Веер
Illuminated display	Bluetooth® Smart	





<sup>\*\*</sup> unfavourable conditions: targets with lower or higher reflectivity or high background illumination or temperatures at the upper or lower end of the specified temperature range.

<sup>\*\*\*</sup> Tolerances apply from 0.05 m to 5 m with a confidence level of 95%. Above 5 m the tolerance may deteriorate according to the values given in the manual of the unit.

## **Scope of Delivery**



#### Leica DISTO™ D1

Art. No. 843418

Art. No. 846805 for U.S. Art. No. 846806 for Japan

Leica DISTO™ D1, 2 x AAA batteries, Calibration Certificate Silver, quick start guide

#### **Accessory**

GZM27 stick-on target plate 147 x 98 mm

Art. No. 723774

GLB 30 laser glasses 3 in 1

GLB 10R laser glasses

Art. No. 834534

UC 20 universal charger incl. rechargeable batteries

Art. No. 788956

## **Extended Warranty**



Register your product within 8 weeks of purchase at <a href="https://www.disto.com/warranty">www.disto.com/warranty</a> and benefit from our 3-year warranty.

•



in accordance with IEC 60825-1

L

