

SPECS:



LT20XG

LT180G

LT360G

Accuracy	+/-3mm @10m (1/8" at 30')	+/-3mm @10m (1/8" at 30')	+/-3mm @10m (1/8" at 30')
Visible Distance • Line • Points • With Receiver	<ul style="list-style-type: none"> • 35m (115 ft) • Not Applicable • 75m (250 ft) 	<ul style="list-style-type: none"> • 35m (115 ft) • 70m (230 ft) • 75m (250 ft) 	<ul style="list-style-type: none"> • 35m (115 ft) • Not Applicable • 75m (250 ft)
Laser Power (Class)	<1mW (Class 2)	<1mW (Class 2)	<1mW (Class 2)
Laser Type (Wavelength)	Green (520nm)	Green (520nm)	Green (520nm)
Power Supply	4 x AA	Lithium 3000 mAh, 7.2V	Lithium 2000 mAh, 11.1V
Battery Life	14 Hours	8 Hours	8 Hours
Locked Pendulum Indication	Double Flashes Every 10 Sec.	Double Flashes Every 10 Sec.	Double Flashes Every 10 Sec.
Charging Time	Not Applicable	< 4 Hours (30-minute quick charge provides 2 hrs. operation)	< 4 Hours (30-minute quick charge provides 2 hrs. operation)
Out of Level Indication	Beam Flashes Continuously	Beam Flashes Continuously	Beam Flashes Continuously
Self-Leveling Range	3° +/- 0.5° All Directions	3° +/- 0.5° All Directions	3° +/- 0.5° All Directions
IP Ratings	IP54	IP54	IP54
Operating Temperature Storage Temperature	-10°C to 45°C (14°F to 113°F) -20°C to 60°C (4°F to 140°F)	-10°C to 45°C (14°F to 113°F) -20°C to 60°C (4°F to 140°F)	-10°C to 45°C (14°F to 113°F) -20°C to 60°C (4°F to 140°F)
Tripod Thread	1/4 - 20	1/4 - 20	1/4 - 20; 5/8 - 11
Size (L x W x H)	120 x 60 x 120mm 4.72 x 2.36 x 4.72 in	121 x 70 x 109mm 4.75 x 2.75 x 4.25 in	145 x 89 x 160mm 5.7 x 3.5 x 6.3 in
Weight	0.6kg (1.2 lbs.)	0.7kg (1.4 lbs.)	1.0kg (2.2 lbs.)
Warranty	2 YRS.	Product 2 YRS. / Battery 1 YR.	Product 2 YRS. / Battery 1 YR.